



- M-2 dynamic microphone for enhanced noise cancelling
- Full flex boom for precise microphone placement
- Collapsible design for compact storage
- One-year Warranty – Backed by industry leading customer service
- Made in USA

### TECHNICAL DATA

<b>Ear coupling</b>	On-the-ear
<b>Hardware</b>	Lightweight alloy
<b>Connector Type</b>	U-174/U
<b>Connection Cable</b>	0.155" (4-mm) OD shielded cable, length ~ 5 ft. (1.5 m)
<b>Weight w/o cable</b>	~ 8.4 oz. (238 g)
<b>Operating temperature</b>	-20°C to +55°C
<b>Dome type</b>	ABS
<b>Characteristic SPL</b>	~95 dB SPL (1 kHz, 1 mW) @ maximum volume nominal
<b>Contact pressure</b>	~0.6 lb. (2.7 N)
<b>Total harmonic distortion (THD)</b>	< 1% - 110 dB SPL (300 - 3,000 Hz)
<b>Transducer principle</b>	Dynamic
<b>Ear Impedance</b>	100 Ω mono
<b>Ear Freq Response</b>	12 - 15,000 Hz
<b>Microphone principle</b>	Dynamic
<b>Mic Impedance</b>	5Ω nominal
<b>Mic Sensitivity</b>	325uV+/-6dB into 5Ω load @ 1kHz for 114 dB SPL input
<b>Mic Freq Response</b>	150 - 8,000 Hz

### DC PRO-2 Headset

#### FEATURES AND BENEFITS

- Dual volume controls provide independent listening levels in each ear
- Adjustable suspension assembly for personalized fit
- Plush, leatherette head pad with breathable, vented design
- Ultra-soft, Dura-Stitched, leatherette ear seals with supra-aural (rest on ear) design provide personalized fit and eliminate heat buildup for greater comfort
- Swivel hinge stirrups for secure, comfortable fit

