



Series 9900 Wireless Intercom System
 Belt Station/VOX (Intercom Only)
 Model No. U9913-BSW
 (Part No. 40992G-07)



U9913-BSW: Belt Station/VOX

FEATURES AND BENEFITS

- Hands-free, full-duplex, voice-activated (VOX) intercom communication
- DECT 6.0 based technology, provides secure signaling, prevents unwanted interception and/or cross talk with other systems or work groups
- Accommodates any Series 9900 Wireless Headset
- Controls include a power button with bi-color LED, VOX adjustment for effective mic control, and a large PTT for VOX override
- VOX “helper” tone guides the user to optimal setting for any high-noise environment through rotary switch adjustment
- High-Visibility Yellow rubberized protective skin included for added impact protection (oil, water, UV resistant)
- Voice prompts help to ensure wireless link status
- Marine-grade, water-tight, impact-resistant enclosure for rugged durability and reliability
- 360° rotational belt clip for versatile attachment and access options
- Water-tight battery compartment houses easily removable, rechargeable Li-Polymer battery, allowing the Belt Station to stay in service with a spare cell while charging

DESCRIPTION

The Series 9900 Wireless Intercom System is the perfect solution for wireless intercom communications in demanding environments, such as airline/airport operations, fire/rescue applications, marine intercom, or any application requiring rugged, secure and reliable communications in and around high-noise areas.

The U9913-BSW VOX Belt Station provides the same functionality as the U9910-BSW, except that the PTT button acts as an intercom-only VOX override, and does not transmit to ancillary devices connected to the system Gateway, such as an aircraft interphone or mobile radio.

It is designed as a wireless interface, or portable part, between a headset and a wireless system Gateway or Controller. Users link to the Gateway or Controller through close-proximity linking with their individual belt stations.

A Bi-Color LED, located on the on/off/link button, provides the status of the user's wireless link, intercom PTT transmit, and battery charge. Each belt station is powered by a replaceable, rechargeable Lithium Polymer battery, which provides 24 hours of continual use.

With its valuable and practical versatility, robust construction and ease of use, the U9913-BSW provides crisp, clear communication with confidence.

TECHNICAL DATA

Weight	10oz/280g (with battery)
Frequency	1920 MHz - 1930 MHz
Average Power Output	4mW (100mW peak) in U.S.
Range	100m (300') line-of-sight, typical
Carriers	5 each (1,728 kHz spacing)
Time Slots	2 x 12 (up and down stream)
Operating Temp.	-10°C to +45°C
Storage Temp.	-20°C to +60°C
Dimensions, Enclosure	4" H x 2-3/4" W x 1-7/8" D (2-1/2" D with belt clip)
Power Source	Li-Polymer rechargeable 3.7V cell, 2000mAh
Power Consumption/ Current Draw	100mA, typical