



**U3801: Remote Headset Station**

## DESCRIPTION

The Series 3800 Vehicle Intercom System is engineered to solve the problem of communicating in high-noise environments with a mobile vehicle platform. Fire apparatus, rescue vehicles, ambulances, command and control vehicles, airline deicers and paint strippers are but a few applications that currently benefit from the Series 3800 system.

The U3801 is a simple headset station, used to expand the intercom system beyond the Master Station. It is designed for use at the end of a series of headset stations, as there are no available connections for “daisy-chaining” additional modules.

It includes one headset jack and headset listen level control, as well as one system input connector for running a C38-xx Jumper Cord from another intercom module.

With a modular design, rugged and weather-resistant enclosures, and functional versatility, the Series 3800 intercom system is an ideal solution for any mobile environment requiring crisp, clear communication and effective hearing protection.

## FEATURES AND BENEFITS

- Provides crisp, clear communication in demanding environments
- Hands-free, full-duplex, intercom communications
- Compatible with all 3000 Series Headsets
- Accommodates one headset user (should be installed where radio transmit function is not required)
- Headset jack with weather-protected, sealed spring cap when not in use
- Headset listen level control for fine-tuning headset volume
- 1 each System Input/Output connector, MS-type with protective cap
- Surface mount installation kit included
- Designed to be installed for single user not requiring radio transmit capability
- Durable, weather-resistant enclosure
- Quality materials, components and craftsmanship
- Rugged and reliable

## TECHNICAL DATA

<b>Power Requirements</b>	12 or 24 VDC (via U3800)
<b>Enclosure</b>	Heavy-gauge polycarbonate (-80° to +212°F)
<b>Volume Control</b>	1 each Headset listen level control
<b>Headset Interface</b>	12B Jack, ¼" (w/ sealed spring lid)
<b>System Connection</b>	1 each, via C38-xx Jumper Cord
<b>Installation</b>	Surface mount (mounting kit included)
<b>Weight</b>	9.2oz./261g
<b>Dimensions</b>	3-¼"L x 4-¾"W x 3"D