



Series 9900 Wireless Intercom System

Power Supply Cord Kits (AC, DC Sources)
For A99-14CRG Charging Unit
C99-14 Series

C99-14AC1 (110VAC)



Consists of the following components:

- Power Cord (7.5 ft/2.3 m)
 - 3 conductor, grounded plug for 110VAC outlet (Type B)
 - IEC320 C13 connector
- Power Adapter Cord (5 ft/1.5 m)
 - Maximum power: 20W
 - Output Voltage: 5VDC
 - Maximum Load: 4A
 - Input Range: 100 to 240VAC, 47-63Hz
 - Output Connector: Switchcraft 760
 - Input Connector: IEC320 C13

C99-14AC2 (230VAC)



Consists of the following components:

- Power Cord (6.5 ft/2 m)
 - 2 conductor, grounded plug for 230VAC (Type CEE 7/7, compatible with Type E or Type F)
 - IEC320 C13 connector
- Power Adapter Cord (5 ft/1.5 m)
 - Maximum power: 20W
 - Output Voltage: 5VDC
 - Maximum Load: 4A
 - Input Range: 100 to 240VAC, 47-63Hz
 - Output Connector: Switchcraft 760

C99-14DC1 (5-15VDC)



Consists of the following components:

- Power Cord (20 ft/6.1 m)
 - Input: Prepared leads
 - Output Connector: Switchcraft 760
- Fuse Kit
 - 5A Slo-Blo fuse
 - Waterproof fuse holder assembly
 - 20 AWG wire segment w/ shrink tubing

C99-14DC2 (15-28VDC)

NOTE: 10 foot version – C99-14DC3



Consists of the following components:

- Power Cord (10 ft/3 m)
 - Input: Prepared leads
 - Output Connector: Switchcraft 760-type
- Power Cord (20 ft/6.1 m), Prepared leads, both ends
- Fuse Kit
 - 5A Slo-Blo fuse
 - Waterproof fuse holder assembly
 - 20 AWG wire segment w/ shrink tubing
- DC/DC Converter (5V, 5A)
 - Input Voltage: 8 to 36VDC
 - Output Voltage: 5VDC +/- 0.1VDC
 - Input/Output Connections (2 terminal screws, 14-24 AWG)
 - Dimensions: 4.73" L x 2.17" W x 1.3"H
 - Protection: Overload, Over Temperature, Reverse Polarity

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 800-298-6235 • Fax: 508-753-5827
• Email: sales@davidclark.com • Web site: www.davidclark.com