



WWW.DAVIDCLARK.COM

Series 9900 Wireless Intercom System

Model A99-14CRG
Battery Charging Unit, 4-Bay
Product Bulletin

The A99-14CRG is a next-generation four-bay battery charger designed for 3.7V Li-Polymer batteries (DCCI p/n: 40688G-90), used with the Series 9900 Wireless Intercom System. Each battery is charged independently, and anywhere from one to four batteries may be charged at a time. A full charge for a depleted battery is achieved in 3-4 hours, and a multi-color LED indicates charge status. Power cable options are sold separately and are available in a variety of AC and DC configurations.



POWER OPTIONS



110VDC
(C99-14AC1)



230VDC
(C99-14AC2)



12VDC
(C99-14DC1 [20'] or C99-14DC3 [10'])



24VDC
(C99-14DC2)

KEY FEATURES

- Provides independent charging for up to 4 each Li-Polymer batteries (40688G-90)
- Expanded DC input range (5 to 15VDC), eliminates the need for DC/DC converter on 12VDC applications
- Battery Holders; NFPA compliant for Fire/EMS applications, eliminating the need for tie-down straps
- Independent multi-color LED's provide visual indication of charge status for each battery
- 3-4 hour charge cycle from depletion to full charge
- Various power cord options available for AC or DC sources (sold separately)
- Permanent and portable mounting options included
- Rugged and reliable, Made in the USA

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 508-751-5800 • Fax: 508-753-5827

• Email: sales@davidclark.com • Web site: www.davidclark.com



Made in USA
19546P-24 (3-14)