



Series 9900 Wireless Intercom System

Push-Back Gateway
 Model No. U9920-GPB
 (Part No. 40993G-01)



U9920-GPB: Push-Back Gateway

FEATURES AND BENEFITS

- Hands-free, full-duplex intercom communication
- DECT 6.0 based technology, provides secure signaling, prevents unwanted interception and/or cross talk with other systems or work groups
- Accommodates up to four (4) wireless belt stations simultaneously connected with audio
- Controls include a power button for close-proximity linking, system volume control for proper overall system gain setting
- Aircraft interphone adapter cords required for flight deck communications (see below)
- High-visibility orange skin included for added impact protection (oil, water, UV resistant)
- “Remove Before Flight” warning banner and lanyard with nylon hook included
- Marine-grade, water-tight, impact-resistant enclosure for rugged durability and reliability
- Multiple Gateways able to function within same RF vicinity with no cross-talk
- Easy, seamless integration to aircraft interphone

DESCRIPTION

The Series 9900 Wireless Intercom System is the perfect solution for wireless intercom/radio communications in demanding environments and applications requiring rugged, secure and reliable communications in and around high-noise areas; ideal for push-back operations, wing-walkers, marshalling agents, maintenance mechanics or de-icing operations.

The U9920-GPB Push-Back Gateway is designed specifically for seamless integration with aircraft interphone systems. It acts as a relay for all intercom audio between multiple Wireless Belt Station/Headset users and the interphone system.

A single Gateway can accommodate up to four (4) connected wireless users at a time with hands-free, full-duplex intercom between a single work group, and Push-To-Talk (PTT) capability for communicating directly with the flight deck.

The U9920-GPB is powered by a Li-Polymer rechargeable battery, capable of 24 hrs of continual usage between charges, and removable from its water-tight compartment within the RF shielded, marine-grade enclosure.

TECHNICAL DATA

Weight, Enclosure	10oz/280g (with battery)
Frequency	1920 MHz - 1930 MHz
Average Power Output	4mW (100mW peak)
Range	100m (300') line-of-sight, typical
Carriers	5 each (1,728 kHz spacing)
Time Slots	2 x 12 (up and down stream)
Operating Temp.	-10°C to +45°C
Storage Temp.	-20°C to +60°C
Power Source	Li-Polymer rechargeable 3.7V cell, 2000mAh
Power Consumption/Current Draw	100mA, typical
Dimensions	4" H x 2-3/4" W x 2-1/2" D
Aircraft Interface Cords (required for flight-deck communications)	41035G-02 (PJ-051 type plug) 41035G-03 (U-174/U, Civilian) 41035G-04 (Dual G.A. Plugs) 41035G-05 (U-174/U, Military)

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 800-298-6235 • Fax: 508-753-5827
 • Email: sales@davidclark.com • Web site: www.davidclark.com

*Technical data subject to change without prior notice.
 Current data available at www.davidclark.com*