



Digital Intercom System Options For Remote PTT (from U9111)

C91-20RD



40892G-19: Radio Interface Cable Assembly: 20 foot length, 6 pin JAE connector on one end (IP-68 sealed), prepared leads on other end. 6 conductor twisted pair shielded cable, 28 AWG, PVC insulation, polyurethane outer jacket, 0.188 inch O.D. **Provides contacts for Single or Dual Remote PTT (1 each required for all remote PTT requirements.)**

40833G-01



Waterproof Throttle PTT Cable Assembly: 15 foot length, over-molded assembly, prepared leads on cable end. 2 conductor cable, 18 AWG, neoprene jacket/insulation, 0.235 inch O.D. 1-2 lb. actuation force. Compliant to MIL-S-13484B (voltage drop, overload, high voltage, open circuit resistance, endurance, waterproofness, extreme temperature resistance); MIL-STD-202A (corrosion resistance, shock resistance, vibration resistance); MIL-F-13927 [90 days](fungus resistance)

26619P-29



Momentary PTT Switch: panel-mount style, SPST/NO type, sealed, non-illuminated, rounded red button, IP-68 (MIL-S-8805/3), aluminum alloy case (2001-T3, anodized IAW MIL-A-8625), glass-filled nylon plunger, solder pin termination, voltage rating – 115VAC, 28VDC; current rating – 10 A, 500K cycle life, actuation force – 3 to 5 lb; supplied with nut and lockwasher

13145P-12



Pushbutton Sealing Boot/Nut Assembly: Silicone rubber (A-A-59588), 60 durometer, IP-68 protection (under normal conditions), color – black, mounting nut – nickel-plated brass (corrosion resistant), temp range: -93°F to +400°F, pressure range: 15psi (internal/external), ½-32UNS-2B bushing thread size, 0.565" button height. Resistant to salt spray, sunlight, ozone, weather, fungus and most acids and lubricating oils.

17836P-06



Liquid-Tight Cable Fitting: Straight-thru, ½ NPT thread size/type, cable diameter range: 0.170" to 0.470", nylon 6/6 w/ TPE sealing gland, IP-68 rated (70 PSI, 5 BAR), temp range: -40°F to +239°F (static), -4°F to +212°F (dynamic), **Locknut not included (see below)**

40688G-78



Locknut (10/pk) – for 17836P-06 Cable Fitting: ½ NPT thread size/type, .265" thick, color – black, nylon 6/6, temp range: -22°F to +221°F

David Clark Company Incorporated
360 Franklin Street, Box 15054
Worcester, MA 01615-0054
Phone: 508-751-5800 Fax: 508-753-5827
www.davidclark.com