

Aviation Headset Specifications

Model No. H10-66XL / P/N 40614G-05

ENC Headset-Mic, Dual Impedance

NSN 5965-01-519-6398



Earphone Type:	Dynamic (ENC)	Microphone:	M-101 Amplified Dynamic or non-amplified
Earphone Impedance:	150 ohms (300 Ohms each; wired in parallel)	Mic Impedance:	5 ohms +/- 20%
Earphone Sensitivity:	90 dB SPL on flat plate coupler, re 1mW input @ 1KHz	Mic Sensitivity:	Non-amplified = .07 – 14mV @ 1kHz for 103dB SPL input or Amplified = 400mV +/- 6dB into 150 ohm load @ 1kHz for 114dB SPL input
Earphone Frequency Response:	100 – 5,500 Hz	Mic Freq Response:	300 – 3000Hz
Boom Type:	Hybrid flex/wire	Comm Cord:	5 ft. coil
Headpad/Hardware:	Super-soft, foam	Plug Type:	U-174/U
Ear Seal:	Undercut, comfort-gel	Weight:	24 oz.

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 800-298-6235 • Fax: 508-753-5827

• Email: sales@davidclark.com • Web site: www.davidclark.com



Made in USA