


H3392: Headset-Mic

DESCRIPTION

Series 3300 Headsets are designed to provide crisp, clear communications and effective hearing protection in high-noise environments. They are engineered to be compatible with David Clark Series 3100, 3400 and 3800 Intercom Systems and Series 3000 Mobile Radio Adapters.

The Model H3392 is a single-ear, over-the-head style headset capable of affording comfort and communication clarity over long periods of time. It utilizes the DC-1A amplified dynamic, noise-cancelling microphone, delivering excellent speech intelligibility.

The single noise-attenuating ear cup provide clear isolated reception of the connected parties by either intercom or radio. A microphone on/off switch is also included.

Durable construction and quality components are found throughout the Series 3300 headsets, with enhanced comfort features for exceptional comfort in any temperature or environmental conditions. David Clark created the world's first noise attenuating communication headsets, and continue to lead the world in delivering quality communication tools.

FEATURES AND BENEFITS

Crisp, clear communication in demanding environments

Single-ear, over-the-head style

Provides isolated reception and exceptional speech intelligibility

Rugged and reliable

Made in the USA

DC-1A amplified dynamic, noise-canceling microphone

Hinged wire boom assembly, 280° rotational, for perfect microphone placement on left or right side

Dynamic earphone element

Microphone on/off switch

Adjustable headband spring assembly for custom fit

Pivoting stirrup assembly helps ensure a precise fit

Foam filled ear seal, durable and comfortable over long hours and in all weather conditions

Pillow headpad and temple pad assemblies provide years of comfort

TECHNICAL DATA

Weight (w/o cord)	9.9oz/280g
Comm Cord	30" straight cord, with 1/4" stereo plug
Certified NRR (3rd party)	No NRR (single-ear)
Dome Type	Lightweight, ABS composite
Hardware	Carbon steel, chrome finish
Ear Impedance	300Ω, nominal
Ear Sensitivity	90dB SPL re 1mW @ 1kHz
Ear Freq Response	200-5,500 Hz
Mic Impedance	150Ω nominal
Mic Sensitivity	400mV+/-6dB into 150Ω load @ 1kHz for 114 dB SPL input
Mic Freq Response	150Hz – 8kHz
Mic DC Supply V., Source Resistance	8-16V, 220 – 2,200Ω, not polarity sensitive