

Series 9900 Wireless Intercom System

Wireless Headset-Mic Model No. H9941 (Part No. 40991G-02)



H9941: Headset-Mic

DESCRIPTION

The Series 9900 Wireless Intercom System is the perfect solution for wireless intercom communications in demanding environments, such as airline/airport operations, fire/rescue applications, marine intercom, or any application requiring robust, reliable and secure communications in and around high-noise areas.

The H9941 is a wireless, marine-grade version of our legacy noise-attenuating headsets, providing the same rugged dependability but designed for use with David Clark Wireless Belt Stations.

It is a single-ear, behind-the-head style communication headset (designed for used under protective head gear), incorporating a noise-canceling dynamic microphone which is optimal for noise environments up to 125 dB.

With superlative performance and unsurpassed comfort features allowing for ease of use over long work shifts, the H9941 is an ideal headset choice for use where high noise levels make it difficult to communicate and effective hearing protection is desired.

FEATURES AND BENEFITS

- Crisp, clear communication in demanding environments
- All hardware marine-grade stainless steel for rust/corrosion resistance in harsh marine environments
- M-2 dynamic microphone, water-resistant protection and superlative noise cancellation
- Hybrid hinged wire/flex mic boom, for perfect microphone placement
- Dynamic earphone (titanium nitride driver) with stainless steel retainer (one slotted dome with no earphone, to allow hearing of ambient sounds)
- Volume control, water-tight, for variable gain setting capability
- 6' extended coil cord with military-grade, 7-pin Belt Station connector
- Undercut, Comfort-Gel ear seals provide unsurpassed comfort and enhanced noise-attenuation (earphone side)
- Nylon overhead support assembly with velcro adjustment for all head sizes
- Reversible hardware, 280° rotational mic boom provide options for microphone positioning (left or right)
- No NRR (single-ear headset)

TECHNICAL DATA

Weight	14.7oz/417g
Comm Cord	6 foot coil, with MAP-57-50
	connector
Certified NRR (3rd party)	N/A
Dome Type	Lightweight, ABS
Hardware	Stainless-steel (18-8)
Potentiometer	220 ohm +/- 20%
Ear Impedance	35 ohm +/- 10% @ 1kHz
Ear Sensitivity	100 dB SPL/1mW @ 1kHz
Ear Frequency	20Hz to 20kHz
Response	
Microphone Principle	Dynamic
Mic Impedance	5 ohm, nominal
Mic Sensitivity	325uV +/-6dB into 5 ohm load
	@ 1kHz for 114 dB SPL input
Mic Frequency	150Hz to 8kHz
Response	

360 Franklin Street, Box 15054, Worcester, MA 01615-0054
Tel: 800-298-6235
Fax: 508-753-5827
Email: sales@davidclark.com
Web site: www.davidclark.com